

Netgear GS108PP



Switch for ART camera network

Compatibility	ARTTRACK5, ARTTRACK5/C
Maximum number of cameras	7
Uplinks to Controller	1
Shape	23.6 x 10.2 x 2.7 cm, Mounting brackets for 1U rackmount included

Technical Data

HARDWARE		
FRONT	10/100/1000 BASE-T RJ45 ports	8
	PoE/PoE+ 802.3af/802.3at Ports	8
	PoE Budget/PSU	PoE Budget: 123WPSU: 130W
REAR	Power Supply	Interchangeable External Power Supply

ADDITIONAL SPECIFICATIONS and CERTIFICATIONS	
Width x Depth x Height (cm // inches)	23.6 x 10.2 x 2.7 cm // 9.29 x 4.02 x 1.06 in
Weight (kg // lb)	0.6 kg // 1.32 lb
Power Consumption	Input 54V 2.4A (130W)
Operating temperature (°C // °F)	0° to 40°C // 32° to 104°F
Fans	Fanless
Certifications	47 CFR FCC Part 15, SubpartB, Class A ICES-003:2016 Issue 6, Class A ANSI C63.4:2014 55032:2012+AC:2013, Class A EN 55024:2010; EN 61000-3-2:2014, Class A; EN 61000-3-3:2013 AS/NZS CISPR 32:2015, Class A VCCI-CISPR 32:2016, Class A KN 35; CNS 13438
Safety Certifications	CB. IEC 60950-1:2005(ed.2) + A1:2009 + A2:2013 UL/cUL Listed; UL60950-1, 2nd Ed. 2014; CAN/CSA C22.2 No. 60950-1-07, 2nd Ed. 2014 EN 60950-1: 2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 AS/NZS 60950.1:2015 KN 32; CNS 14336 -1

For more detailed information look at the Netgear data sheet:

https://www.netgear.com/images/datasheet/switches/GS108LP_GS108PP_GS116LP_GS116PP_DS.pdf