



	SMARTTRACK3	SMARTTRACK3-IF	SMARTTRACK3/M	SMARTTRACK3/M-IF
Tracking volume	small to medium tracking volumes	small to medium tracking volumes Also tracks in sunlit areas	small tracking volumes	small tracking volumes also tracks in sunlit areas
Ideal for...	For all tracking purposes in small volumes (e.g. VR applications with head tracking and Flystick at small Powerwalls or CAVEs)		optimized for tracking in simulators or inside car or airplane cockpits	
Image Sensor	1280 x 1024 Pixel			
Benefits	<ul style="list-style-type: none"> mobile and compact all-in-one system controller/all processing integrated cost efficient tracking system OS support of the GUI: Windows (0,11,...), Linux... 	see SMARTTRACK3, plus: <ul style="list-style-type: none"> also tracks in sunlit areas 	benefits in addition to SMARTTRACK3: <ul style="list-style-type: none"> even smaller more robust against vibrations optimized mounting for integration alternative lenses for narrow field of view allows shorter tracking distances, i.e., the user can get closer less weight, means: less G-powers 	see SMARTTRACK3/M, plus: <ul style="list-style-type: none"> also tracks in sunlit areas
Frame rate (sensor)	150 Hz @ full frame, up to 240 Hz with reduced tracking volume			
Image processing	integrated			
Status indicator	2 LEDs; dimmable			
IR source	high power LEDs, 850nm, adjustable in intensity (exempt group according to IEC62471-1)			
Filters	longpass	bandpass	longpass	bandpass
Effective transmission	795 - 1100 nm	845 - 859 nm	795 - 1100 nm	845 - 859 nm
Suppression in rejection regions	avg. > 10 ⁴ – 10 ⁵	avg. > 10 ⁶	avg. > 10 ⁴ – 10 ⁵	avg. > 10 ⁶
Data transfer, sync and power supply	single cable solution data: Gigabit Ethernet power: PoE (IEEE 802.3af-2003) via max. 100 m RJ45 cable (CAT5)			
Size (W & H & D)	approx. 381 x 54 x 93 mm		approx. 280 x 40 x 90 mm	
Weight	approx. 1.5 kg		approx. 1.0 kg	
Cooling	passive, noiseless			
Operation temperature	0...35° C (when used on the car dashboard in bright sunlight, heat protection should be established)			
Relative humidity	5...85% (non-condensing)			
Power consumption	12 W			
Mounting	ceiling mount with a standard tripod thread		additional mounting option with brackets	
Compatibility	cascade between SMARTTRACKs and ARTTRACKs			
	peripherals: targets, LP-Research, Manus gloves, Measurement Tool, Flystick not supported: Fingertracking, Motion Capture			